## 70cm Undermount RANGEHOOD

PRODUCT CODE: EP70UMS2



### **FEATURES:**

- + 430 Grade Stainless Steel Bottom Panel
- + 3 Speed Air Function
- + 700m3/h Extraction capacity
- + 2 x 1.5w LED Light
- + Separate Light Function

- + Decibel rating 48-58 dBA
- + 150mm flue diameter

### FLUSH UNDERMOUNT INSTALLATION

This model once installed into the cabinet will sit flush which conceals the remainder of the rangehood, providing a clean and modern look for your rangehood.

### SOFT TOUCH UNDERMOUNT CONTROLS

This rangehood provides a Soft Touch Button system designed for easy usage.

## HIGH EXTRACTION CAPACITY

The extraction capacity of 700m3/hr provides strength and power to this stylish rangehood.

### DISHWASHER SAFE CASSETTE FILTERS

The cassette filters can be placed in a dishwasher for easy cleaning and can easily be removed, re-connected from the rangehood.

# Electrical Requirements Rangehood is supplied with 10amp cord & plug. Decibel Rating 48-58 dBA Available Ventilation Kits Wall – Eave vent kit RHKE65EU Universal metal roof kit (includes flashing) RHKTR65EU Universal tile roof kit (includes flashing) Carbon Filter CF110 (requires 2)

9347726027944





### **HELPFUL TIPS**


- Leave your rangehood on for 15 minutes after the cooking of the food to remove all odors, steam etc.
- The dishwasher-safe cassette filters need to be cleaned after approximately 2 months of standard operation
- It is recommended that the rangehood be installed between 650mm and 750mm above the cooktop
- It is also recommended that fumes from the rangehood be ducted out into the atmosphere.
- + Turn off the rangehood before attempting to clean

### INSTALLATION

Installation is recommended by a qualified installer, please refer to the product manual for full installation instructions.

### FILTER CLEANING INFORMATION

Cassette mesh filter: Requires cleaning monthly. This will ensure no interruptions with airflow operation.



**Barcode**